

## Catalogue

## Chapter

## Model

PS-50/200 TP2 E 230/400/440V 3/3N 50/60H

18003037

19/02/2020

### FLATWORK IRONER, PS-50/200 TP2 E

#### MAINTENANCE CARE

Simple, reliable and accesible mechanism in which the components have been designed and manufactured with the highest quality and prestige.

#### STAINLESS STEEL DESIGN

Panels made of stainless steel and steel with grey coating, inox aesthetic (skinplate), easy to clean and more hygienic.

#### INVERTER

Frequency inverter in all models.

#### TP2 7" TOUCH SCREEN CONTROL

New Touch Plus control with 7" touchscreen which offers great flexibility and ease of use, as well as new features that enable better management of the laundry.

#### HIGH-TECH ROLL

High-performance steel roller.

- Front insertion and reception of linen.
- Variable-frequency drive to control ironing speed.
- Safety protector for hands
- Automatic stop on cooling (80 °C)
- Unit exterior constructed in sandwich panel and stainless steel.
- Powerful exhaust extraction system.
- Insertion and ironing belts in Nomex for easy operation, high quality ironing and great durability.
- Electric heated model.
- 7 ironing speeds, adjustable by variablefrequency drive, for selection between 1.5 and 15 m/ minute.
- Vapour extraction connection of 153 mm diameter.
- Table height of 1030 mm.


#### Options

- Smart system: Moisture control that adapts to the speed of the roller depending on the dampness of the clothes.
- Chromed roll for better performance and durability.
- Folder + Rear exit.
- HPS: High production system.

"Note: You are recommended to insert the linen with a maximum moisture level of 45%."

### DIMENSIONS

X Width	2820 mm	X Gross width	3075 mm
Y Depth	1160 mm	Y Gross depth	1170 mm
Z Height	1420 mm	Z Gross height	1675 mm
Net Weight	930,0 kg	Gross Weight	960,0 kg
Net volume	4,650 m3	Gross volume	6,026 m3



### ELECTRICITY TECHNICAL SPECIFICATIONS

Engine power	0,37 kW
Fan Motor Power	0,25 kW
Electric power	32,120 kW
Amperage (A)	50A
Heating power	31,50 kW
Voltage	230/400/440V - 3/3N
Electric frequency	50/60Hz

### AIR TECHNICAL SPECIFICATIONS

Maximum airflow	600 m3/h
-----------------	----------

### CONNECTIONS TECHNICAL SPECIFICATIONS

230 V three-phase wiring	4 X 35 / 100A
Three-phase +N 400V wiring	5 X 10 / 50A
Extraction 1 diameter	153,00 mm

### OTHERS

Roller length in cm	200,00 cm
Roller diameter	500 mm
Production 45% moisture	50 - 70 kg/h
Operational speed	1,00 - 8,00 m/min
Noise level	65,00 dB